Oracle® Collaboration Suite

Quick Installation Guide

10g Release 1 (10.1.2) for HP-UX PA-RISC (64-Bit)

B25469-02

March 2006



Oracle Collaboration Suite Quick Installation Guide 10g Release 1 (10.1.2) for HP-UX PA-RISC (64-Bit) B25469-02

Copyright © 2005, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software-Restricted Rights (June 1987). Oracle Corporation. 500 Oracle Parkway. Redwood City. CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Introduction

This guide describes how to install Oracle Collaboration Suite.

Contents of this Guide

- Documentation Accessibility
- Installation Types Covered in This Guide
- Starting the Installer
- Performing Basic Installation
- Performing Infrastructure and Applications Installation
- Performing Multiple-Computer Installation
- Postinstallation Tasks
- Checking Requirements
- Accessing the Welcome Page
- Additional Resources

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

http://www.oracle.com/accessibility/

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Installation Types Covered in This Guide

This guide is intended for users who want to install Oracle Collaboration Suite in these configurations:

- Oracle Collaboration Suite Infrastructure and Applications Installation on a Single Computer
 - This topology installs Oracle Collaboration Suite on one computer. Both Oracle Collaboration Suite Infrastructure and Oracle Collaboration Suite Applications are installed on the same computer.
- Multiple-Computer Installation

This topology installs Oracle Collaboration Suite Infrastructure on one computer and Oracle Collaboration Suite Applications on a separate computer.

If you want more complex topologies, read the *Oracle Collabo*ration Suite Installation Guide for hp-ux for complete installation instructions.

Before installing Oracle Collaboration Suite, you should read the *Oracle Collaboration Suite Release Notes for hp-ux* for the latest information.

Starting the Installer

In the following instructions, the disc mount point is referred to as /DVD. If your mount point is different, substitute the correct mount point name for all references to /DVD.

To start the installer:

- Ensure that you have checked all the minimum requirements listed in Checking Requirements.
- Log in to the computer as the user who will install Oracle Collaboration Suite.
- Insert the disk:

Insert the Oracle Collaboration Suite DVD.

- If your computer does not have automount capability, see Mounting the DVD-ROM for steps on mounting the DVD-ROM manually.
- **5.** Start up the installer:

Note: Do not run the installer from the mount point directory. Note the "cd" command below; it changes your current directory to your home directory so that you do not start up the installer from the mount point.

DVD-ROM:

```
prompt> cd
prompt> /DVD/collaboration_suite/runInstaller
```

This launches Oracle Universal Installer, through which you can install Oracle Collaboration Suite.

Mounting the DVD-ROM

Follow these steps if your computer does not automatically mount the DVD-ROM:

- **1.** Insert the DVD.
- 2. Log in as the root user.

```
prompt> su
Password:
```

3. Create the DVD-ROM mount point directory:

```
prompt> /usr/bin/mkdir /DVD
```

4. Mount the DVD-ROM drive on the mount point directory:

```
prompt> /usr/sbin/mount -F cdfs -o rr /dev/dsk/cxdytz
/DVD
```

In the preceding example, /DVD is the disc mount point directory and /dev/dsk/cxdytz is the device name for the disc device, for example /dev/dsk/c0d2t0.

5. Log out from the root user.

```
prompt> exit
```

Performing Basic Installation

To install Oracle Collaboration Suite on one computer using the Basic installation method:

- 1. Start the installer. See Starting the Installer for details.
- 2. Select Installation Method screen

Basic Installation: Select this installation method to quickly install Oracle Collaboration Suite. This installation method requires minimal user input. It installs the software using the following information that you specify on this screen:

- Installation Directory: Specify the full path to the directory where you want to install the software (the Oracle home directory).
- Password: Specify a common password for the administrative accounts (schema).
- Confirm Password: Reenter the password you specified previously to confirm that it is correct.
- Click Select Components to display the Select Components to Configure screen. This screen allows you to deselect the components that you do not want to configure during the install.

 Click Set Languages to display the Language Selection screen. This screen allows you to select the language in which Oracle Collaboration Suite will be installed.

Note: The default language selected in the Selected Languages list is English. However if the language of the operating system of the computer on which you are installing Oracle Collaboration Suite is not English, then that language will also be automatically added to Selected Languages list. As a result, two languages, English and the locale language of your operating system, will be installed as a part of the basic Oracle Collaboration Suite installation.

Advanced Installation: Select this installation method if you want to:

- Perform a custom software installation, or choose a different database configuration.
- Select an installation type.
- Enable an existing database.
- Select different product languages.
- Specify different passwords for administrative schemas.

Select Basic Installation and click Next.

- **3.** If this is the first Oracle product to be installed on this computer, the installer displays these additional screens:
 - a. Specify Inventory Directory and Credentials screen

Enter the full path of the inventory directory: Enter a full path to the inventory directory. Enter a directory that is different from the Oracle home directory for the product files.

Example: /home/oracle/oraInventory

Specify Operating System group name: Select the operating system group that will have write permission for the inventory directory.

Example: oinstall

Click Next.

b. Run orainstRoot.sh dialog box

Run the orainstRoot.sh script in a different shell as the root user. The script is located in the inventory directory.

After running the script, click **Continue**.

Summary screen

Verify your selections and click Install.

The installer now installs the files.

5. Run root.sh dialog box

Note: Do not run the root. sh script until this dialog box appears.

When you see this dialog box, run the root.sh script in a different shell as the root user. The script is located in the Oracle home directory of this instance.

Note: During the root.sh prompt, you might get some warning messages. Ignore the messages and continue with the installation.

Click OK.

6. Configuration Assistants screen

This screen displays the progress of configuration assistants. Configuration assistants configure Oracle Collaboration Suite components.

7. End of Installation screen

Click Exit to quit the installer.

Note: The information displayed at the end of the installation is also available in the *\$ORACLE_*

HOME/install/setupinfo.txt file. This file contains summarized information about Oracle Collaboration Suite and links to the URLs.

Performing Infrastructure and Applications Installation

This topology installs Oracle Collaboration Suite on one computer, which provides the following components:

- Oracle Collaboration Suite Database
- Identity Management
- Oracle Collaboration Suite Applications

To install Oracle Collaboration Suite on one computer:

- 1. Start the installer. See Starting the Installer for details.
- **2.** <u>Select Installation Method screen</u>
 - Select Advanced Installation and click Next.
- **3.** If this is the first Oracle product to be installed on this computer, the installer displays these additional screens:

a. Specify Inventory Directory and Credentials screen

Enter the full path of the inventory directory: Enter a full path to the inventory directory. Enter a directory that is different from the Oracle home directory for the product files.

Example: /home/oracle/oraInventory

Specify Operating System group name: Select the operating system group that will have write permission for the inventory directory.

Example: oinstall

Click Next.

b. Run orainstRoot.sh dialog box

Run the orainstRoot.sh script in a different shell as the root user. The script is located in the inventory directory.

After running the script, click **Continue**.

4. Specify File Locations screen (Advanced installation only)

Name: Enter a name to identify this Oracle home.

Example: infra_home_10_1_2

Destination Path: Enter the full path to the destination directory. This is the Oracle home. If the destination directory does not exist, the installer creates it.

Example: home/oracle/orainfra

Click Next.

5. Specify Hardware Cluster Installation Mode screen (Advanced installation only)

This screen appears only if the computer is part of a hardware cluster.

When you are installing Oracle Collaboration Suite Infrastructure and Applications, select **Local Installation** because hardware clusters are not supported for Oracle Collaboration Suite Infrastructure and Applications.

Click Next.

- 6. <u>Select a Product to Install screen</u> (Advanced installation only)
 Select Oracle Collaboration Suite Infrastructure and Applications 10.1.2.0.0 and click Next.
- 7. Language Selection screen (Advanced installation only)

This screen enables you to select the language in which Oracle Collaboration Suite components will run.

Select the required language or languages from the Available Languages list and add them to the Selected Languages list.

Click Next.

8. Collaboration Suite Infrastructure and Applications Methodology screen (Advanced installation only)

Read the instructions on the screen carefully.

Click Next.

Select Components to Configure screen (Advanced installation only)

Select the Oracle Collaboration Suite Applications components that you want to install.

Click Next.

Note: If at any time during installation (before you click the **Install** button) you need to make changes to the list of applications that you want configured, then you will have to exit out of the installation and restart it.

10. Specify Namespace in Internet Directory screen (Advanced installation only)

Select suggested namespace and click Next.

Specify Database Configuration Options screen (Advanced installation only)

Global Database Name: Enter a name for Oracle Collaboration Suite Database, and append your domain name to the database name.

Example: orcl.yourcompany.com

SID: Enter the system identifier for the Oracle Collaboration Suite Database. Typically this is the global database name, but without the domain name. The SID must be unique across all databases.

Example: orcl

Specify Database File Location: Specify the full path to the parent directory for the data files directory. The directory you specify must exist, and you must have write permissions to it.

The installer installs the data files in a subdirectory of the path you specify. The installer uses the database name for the name of the subdirectory. For example, if you specify orcl.yourcompany.com for the global database name and /data/dbfiles for the database file location, the installer places database files in the following directory: /data/dbfiles/orcl

Click Next.

12. <u>Specify Database Schema Passwords screen</u> (Advanced installation only)

Set the passwords for the administrative database users, which are privileged accounts used for database administration. You can use the same password for all users, or specify different passwords for each user.

Click Next.

Specify Application Passwords screen (Advanced installation only)

Set passwords for administrative accounts that are created for the applications that you selected during installation.

Click Next.

14. Specify Oracle Mail Domain Information screen (Advanced installation only)

Mail Domain: Specify the local (network) domain for IMAP/SMTP, or other mail protocols.

Click Next.

 Specify Port Configuration Options screen (Advanced installation only)

Select Automatic and click Next.

Note: The Automatic option only uses ports in the range 7777-7877 for Oracle HTTP Server and 4443-4543 for Oracle HTTP Server with SSL. If you need to set the port numbers as 80 for Oracle HTTP Server and 443 for Oracle HTTP Server with SSL, then you must select the **Manually Specify Ports** option.

16. Summary screen

Verify your selections and click **Install**.

The installer now installs the files.

17. Run root.sh dialog box

Note: Do not run the root. sh script until this dialog box appears.

When you see this dialog box, run the root. sh script in a different shell as the root user. The script is located in the Oracle home directory of this instance.

Note: During the root.sh prompt, you might get some warning messages. Ignore the messages and continue with the installation.

Click OK.

This dialog box appears twice for the single-computer installation, once during infrastructure installation and next during the application tier installation.

18. Configuration Assistants screen

This screen displays the progress of configuration assistants. Configuration assistants configure Oracle Collaboration Suite components.

19. End of Installation screen

Click Exit to quit the installer.

Note: The information displayed at the end of the installation is also available in the *\$ORACLE_*

HOME/install/setupinfo.txt file. This file contains summarized information about Oracle Collaboration Suite and links to the URLs.

Performing Multiple-Computer Installation

This topology installs Oracle Collaboration Suite Infrastructure on one computer and Oracle Collaboration Suite Applications on a separate computer.

Setting up the multiple-computer topology involves:

- 1. Installing Oracle Collaboration Suite Infrastructure
- 2. Installing Oracle Collaboration Suite Applications

Because Oracle Collaboration Suite Applications use services from the Oracle Collaboration Suite Infrastructure, you must install the infrastructure first.

Installing Oracle Collaboration Suite Infrastructure

To install Oracle Collaboration Suite Infrastructure with a new database and a new Oracle Internet Directory:

- 1. Start the installer. See Starting the Installer for details.
- 2. Select Installation Method screen

Select Advanced Installation and click Next.

- **3.** If this is the first Oracle product to be installed on this computer, the installer displays these additional screens:
 - a. Specify Inventory Directory and Credentials screen

Enter the full path of the inventory directory: Enter a full path to the inventory directory. Enter a directory that is different from the Oracle home directory for the product files.

Example: /home/oracle/oraInventory

Specify operating system group name: Select the operating system group that will have write permission for the inventory directory.

Example: oinstall

Click Next.

b. Run orainstRoot.sh dialog box

Run the orainstRoot.sh script in a different shell as the root user. The script is located in the inventory directory.

After running the script, click **Continue**.

4. Specify File Locations screen (Advanced installation only)

Name: Enter a name to identify this Oracle home.

Example: infra_home_10_1_2

Destination Path: Enter the full path to the destination directory. This is the Oracle home. If the destination directory does not exist. Oracle Universal Installer creates it.

Example: home/oracle/orainfra

Click Next.

5. Specify Hardware Cluster Installation Mode screen (Advanced installation only)

This screen appears only if the computer is part of a hardware cluster.

When you are installing Oracle Collaboration Suite Infrastructure, select Local Installation because hardware clusters are not supported for Oracle Collaboration Suite Infrastructure.

Click Next.

- Select a Product to Install screen (Advanced installation only)
 Select Oracle Collaboration Suite Infrastructure 10.1.2.0.0
 and click Next.
- Select Installation Type screen (Advanced installation only)
 Select Identity Management and Oracle Collaboration Suite Database and click Next.
- Language Selection screen (Advanced installation only)
 This screen enables you to select the language in which Oracle

This screen enables you to select the language in which Oracle Collaboration Suite components will run.

Select the required language or languages from the Available Languages list and add them to the Selected Languages list.

Click Next.

9. <u>Select Configuration Options screen</u> (Advanced installation only)

Select Oracle Internet Directory.

Select OracleAS Single Sign-On.

Select Delegated Administration Service.

Select Oracle Directory Integration and Provisioning.

Do not select OracleAS Certificate Authority.

Do not select **High Availability and Replication**.

Click Next.

10. Specify Namespace in Internet Directory screen (Advanced installation only)

Select suggested namespace and click Next.

11. Specify Port Configuration Options screen (Advanced installation only)

To use default ports for the components, select **Automatic Port** Selection.

If you do not want to use the default ports, then select Manually specify ports and select the component for which you want to select the port.

Note: The Automatic option only uses ports in the range 7777-7877 for Oracle HTTP Server and 4443-4543 for Oracle HTTP Server with SSL. If you need to set the port numbers as 80 for Oracle HTTP Server and 443 for Oracle HTTP Server with SSL, then you must select the **Manually Specify Ports** option.

Click Next.

12. Guest Account Password screen (Advanced installation only)

Enter and confirm the password for the guest account and click **Next**.

13. Specify Database Configuration Options screen (Advanced installation only)

Global Database Name: Enter a name for the Oracle Collaboration Suite Database database, and append your domain name to the database name.

Example: orcl.yourcompany.com

SID: Enter the system identifier for the Oracle Collaboration Suite Database. Typically this is the global database name, but without the domain name. The SID must be unique across all databases.

Example: orcl

Specify Database File Location: Specify the full path to the parent directory for the data files directory. The directory you specify must exist, and you must have write permissions to it.

The installer installs the data files in a subdirectory of the path you specify. The installer uses the database name for the name of the subdirectory. For example, if you specify orcl.yourcompany.com for the global database name and /data/dbfiles for the database file location, the installer places database files in the following directory:

/data/dbfiles/orcl

Click Next.

14. Specify Database Schema Passwords screen (Advanced installation only)

Set the passwords for the administrative database users, which are privileged accounts used for database administration. You can use the same password for all users, or specify different passwords for each user.

Click Next.

15. Specify Instance Name and ias admin Password screen (Advanced installation only)

Instance Name: Enter a name for this instance. Instance names can contain the dollar (\$) and underscore (_) characters in addition to any alphanumeric characters. If you have more than one Oracle Collaboration Suite instance on a computer, the instance names must be unique.

Example: infra

ias_admin Password and Confirm Password: Enter and confirm the password for the ias_admin user. This is the administrative user for this instance.

Passwords must consist of at least five characters, and one of the characters must be a number.

For example: welcome99

Click Next.

16. Summary screen

Verify your selections and click Install.

The installer now installs the files.

17. Run root.sh dialog box

Note: Do not run the root. sh script until this dialog box appears.

When you see this dialog box, run the root. sh script in a different shell as the root user. The script is located in the Oracle home directory of this instance.

Note: During the root.sh prompt, you might get some warning messages. Ignore the messages and continue with the installation.

Click OK.

18. Configuration Assistants screen

This screen displays the progress of configuration assistants. Configuration assistants configure Oracle Collaboration Suite components.

19. End of Installation screen

Click Exit to quit the installer.

Note: The information displayed at the end of the installation is also available in the *\$ORACLE_*

HOME/install/setupinfo.txt file. This file contains summarized information about Oracle Collaboration Suite and links to the URLs.

Installing Oracle Collaboration Suite Applications

Before you start installing Oracle Collaboration Suite Applications, you must perform the preinstallation task discussed in the following subsection.

Preinstallation Task

Before you install the Applications tier, check if sendmail is running by using the following command:

```
prompt> ps -elf | grep sendmail
```

If sendmail is running, shut it down as the root user as follows:

```
prompt> /sbin/init.d/sendmail stop
```

Oracle Collaboration Suite Applications Installation Procedure

The following procedure installs Oracle Collaboration Suite Applications and configures it to use the Oracle Collaboration Suite Infrastructure installed according to the steps explained in Installing Oracle Collaboration Suite Infrastructure.

- 1. Start the installer. See Starting the Installer for details.
- Select Installation Method screen
 Select Advanced Installation and click Next.

- **3.** If this is the first Oracle product to be installed on this computer, the installer displays these additional screens:
 - a. Specify Inventory Directory and Credentials screen (Advanced installation only)

Enter the full path of the inventory directory: Enter a full path to the inventory directory. Enter a directory that is different from the Oracle home directory for the product files.

Example: /home/oracle/oraInventory

Specify operating system group name: Select the operating system group that will have write permission for the inventory directory.

Example: oinstall

Click Next.

b. Run orainstRoot.sh dialog box (Advanced installation only)

Run the orainstRoot.sh script in a different shell as the root user. The script is located in the inventory directory.

After running the script, click **Continue**.

4. Specify File Locations screen (Advanced installation only)

Name: Enter a name to identify this Oracle home.

Example: apptier_home_10_1_2

Destination Path: Enter the full path to the destination directory. This is the Oracle home. If the destination directory does not exist, the installer creates it.

Example: home/oracle/oraapptier

Click Next.

Specify Hardware Cluster Installation Mode screen (Advanced installation only)

This screen appears only if the computer is part of a hardware cluster.

If you are installing Oracle Collaboration Suite Applications, select **Local Installation** because hardware clusters are not supported for Oracle Collaboration Suite Applications.

Click Next.

Select a Product to Install screen (Advanced installation only)
 Select Oracle Collaboration Suite Applications 10.1.2.0.0.

To install additional languages, click **Product Languages**.

Click Next.

7. <u>Language Selection screen</u> (Advanced installation only)

This screen enables you to select the language in which Oracle Collaboration Suite components will run.

Select the required language or languages from the Available Languages list and add them to the Selected Languages list.

Click Next.

8. Select Components to Configure screen (Advanced installation only)

Select the Oracle Collaboration Suite Applications components that you would like to configure during the installation.

Click Next.

Note: If at any time during the installation (before you click the Install button) you need to make changes to the list of applications that you want configured, then you will have to exit out of the installation and restart it.

9. Register with Oracle Internet Directory (Advanced installation only)

Host: Enter the name of the computer where Oracle Internet Directory is running.

Port: Enter the port number at which Oracle Internet Directory is listening. If you do not know the port number, see the portlist.ini file for the port of Oracle Internet Directory. This file is located in the <code>ORACLE_HOME/install</code> directory.

Use SSL to connect to Oracle Internet Directory: Select this option if you want Oracle Collaboration Suite components to use only SSL to connect to Oracle Internet Directory.

Click Next.

 Specify UserName and Password for Oracle Internet Directory screen (Advanced installation only)

Username: Enter the user name to use to log in to Oracle Internet Directory. Use cn=orcladmin as the user name if you are the Oracle Internet Directory Superuser.

Password: Enter the user password.

Click Next.

 Oracle AS Metadata Repository screen (Advanced installation only)

Database Connection String: Select the OracleAS Metadata Repository that you want to use for this application tier instance. The installer will register this instance with the selected OracleAS Metadata Repository.

Click Next.

12. Select Database for Components screen (Advanced installation only)

This screen shows the database to be used for each of the components that you earlier selected in the Select Components to Configure screen.

Click Next.

13. Specify Port Configuration Options screen (Advanced installation only)

To use default ports for the components, select **Automatic Port** Selection.

If you do not want to use the default ports, then select Manually specify ports and select the component for which you want to specify the port.

Note: The Automatic option only uses ports in the range 7777-7877 for Web Cache HTTP Listen port and 4443-4543 for Web Cache HTTP Listen with SSL. If you need to set the port numbers as 80 for Web Cache HTTP Listen port and 443 for Web Cache HTTP Listen with SSL, then you must select the **Manually Specify Ports** option.

Click Next.

14. Specify Administrative Password and Instance Name screen (Advanced installation only)

Instance Name: Specify the name of the OracleAS instance for the Oracle Collaboration Suite administrative accounts.

Administrative Password: Specify the initial password for the Oracle Collaboration Suite administrative accounts.

Confirm Password: Confirm the password.

Click Next.

 Oracle Calendar Server Host Alias screen (Advanced installation only)

Host or Alias: Specify either the host address or the alias of the Calendar server instance.

Note: Oracle recommends that you use alias in place of host name if later you may want to move the Calendar server

instance or change the host name. Specify the host name if an alias is not configured.

Click Next.

16. Specify Oracle Mail Domain Information screen (Advanced installation only)

Mail Domain: Specify the local (network) domain for IMAP/SMTP, or other mail protocols.

Click Next.

17. Summary screen

Verify your selections and click Install.

The installer now installs the files.

18. Run root.sh dialog box

Note: Do not run the root . sh script until this dialog box appears.

When you see this dialog box, run the root. sh script in a different shell as the root user. The script is located in the Oracle home directory of this instance.

Click OK.

19. Configuration Assistants screen

This screen displays the progress of configuration assistants. Configuration assistants configure Oracle Collaboration Suite components.

20. End of Installation screen

Click **Exit** to quit the installer.

Note: The information displayed at the end of the installation is also available in the *\$ORACLE_ HOME/*install/setupinfo.txt file. This file contains summarized information about Oracle Collaboration Suite and links to the URLs.

Postinstallation Tasks

After you have installed Oracle Collaboration Suite Applications, perform the following steps:

- 1. If you have installed Oracle Mail, log in as root.
- **2.** Set ORACLE_HOME.
- **3.** Start the TNS listener as follows:

Checking Requirements

Check that your computer meets the minimum requirements:

- **Checking Hardware Requirements**
- **Checking Software Requirements**
- **Checking Kernel Parameters**
- Creating an Operating System Group for the Inventory Directory
- Creating an Operating System User
- Checking Environment Variables
- Checking If Port 1521 Is in Use

Checking Hardware Requirements

Your computer must meet the hardware requirements mentioned in the following sections.

Processor and Network Requirements

64-bit HP-UX PA-RISC processor.

If the processor is 64-bit the following command returns the value 64:

prompt> /bin/getconf KERNEL_BITS

- 450 MHz or greater processor speed is recommended.
- The computer must be connected to a network. You cannot install Oracle Collaboration Suite on a standalone computer.
- The IP address of the computer must be static. Oracle Collaboration Suite does not support HP-UX systems using dynamic host configuration protocol (DHCP).

Other System Requirements

Table 1 shows other system requirements.

Table 1 Minimum System Requirements

Item	Minimum Requirement	Command	
Memory	Oracle Collaboration Suite Infrastructure: 1 Gigabyte (GB)	<pre>prompt> /usr/sbin/dmesg</pre>	
	Oracle Collaboration Suite Applications: 1 GB		
	Oracle Collaboration Suite Database: 1 GB		
	Note: For Oracle Collaboration Suite Infrastructure and Applications installation on a single computer, 2 GB or more is recommended.		
Disk space	Oracle Collaboration Suite Infrastructure: 9.5 GB	prompt> bdf -k dir Replace <i>dir</i> with the Oracle	
	Oracle Collaboration Suite Applications: 5.5 GB	home directory or with the parent directory if the Oracle	
	Oracle Collaboration Suite Database: 5 GB	home directory does not exist yet.	

Table 1 (Cont.) Minimum System Requirements

Item	Minimum Requirement	Command
Space in /tmp	400 Megabytes (MB)	prompt> bdf /tmp
directory		If the /tmp directory does not have enough free space, you can specify a different directory by setting the TMP environment variable.
Swap space	1.5 GB	prompt> /usr/sbin/swapinfo -a
Monitor	256-color display	prompt> /usr/X11R6/bin/xdpyinfo
		Look for the "Depth" line. You need a depth of at least 8 (bits per pixel).

Checking Software Requirements

Oracle Collaboration Suite is certified with the following Operating System-specific software. For the most current list of supported Operating System-specific software, for example JDK version, Operating System version, check Oracle *MetaLink* at

http://metalink.oracle.com

Complete the following steps before installing Oracle Collaboration Suite on HP-UX 11.11 systems:

1. To determine which version of HP-UX is installed, enter the following command:

```
prompt> uname -a
HP-UX hostname B.11.11 U 9000/800 109444686
unlimited-user license
```

2. Make sure that June 2003 Quality Pack GoldQPK11i is installed. To determine whether the Quality Pack is installed, enter the following command:

```
prompt> /usr/sbin/swlist | grep QPK
```

If the quality pack is not installed, download it from the following web site and install it

```
http://www.software.hp.com/SUPPORT_
PLUS/apk.html
```

3. Check that the following software packages, or later versions, are installed:

- BUNDLE11i B.11.23.0409.3 Required Patch Bundle for HP-UX 11i v2 (B.11.23), September 2004
- PHKL 29198 s700 800 11.11 Psets Enablement Patch: top(1)
- PHSS_28871 s700_800 11.11 ld(1) and linker tools cumulative patch
- PHSS_28880 s700_800 11.11 HP aC++ -AA runtime libraries (aCC A.03.50)
- PHCO 29960 s700 800 11.11 Pthread enhancement and fixes

The following patches are required by JDK 1.4.2.05 or later. JDK 1.4.2.05 is installed with this release. Refer to the HP Support site for a list of all IDK patches.

- PHKL 25842 s700 800 11.11 Thread Abort syscall
- PHKL_25993 s700_800 11.11 thread nostop for NFS, rlimit, Ufalloc fix
- PHKL 25994 s700 800 11.11 detach; NOSTOP, Abrt, Psets; slpq1; FSS; getlwp
- PHKL_25995 s700_800 11.11 ufalloc; VxFS3.5; SPP fragmentation;AIO;EVP

- PHKL_26468 s700_800 11.11 vPar, callout, abstime, shared sync perf
- PHKL_28489 s700_800 11.11 copyin EFAULT, LDCD access type
- PHNE 29887 s700 800 11.11 cumulative ARPA Transport patch

The following patches are required if ANSI C and C++ are installed on the system:

- PHSS 26792 s700 800 11.X ANSI C compiler B.11.11.04 cumulative patch
- PHSS 26793 s700 800 11.X +O4/PBO Compiler B.11.11.04 cumulative patch
- PHSS_31849 : s700_800 11.23 linker + fdp cumulative patch
- PHSS_31852: s700_800 11.23 aC++ Runtime (IA: A.06.05, PA: A.03.65)
- PHSS 32511: s700 800 11.23 HP aC++ Compiler (A.03.63)

- PHSS_32512: s700_800 11.23 ANSI C compiler B.11.11.12 cumulative patch
- PHSS_32513 : s700_800 11.23 +O4/PBO Compiler
 B.11.11.12 cumulative patch

Following patch is required if ServiceGuard is installed on the system:

■ PHSS_32740: s700_800 11.23 Serviceguard A.11.16.00

The following patches are required for Real Application Clusters:

- MC/ServiceGuard A.11.09 OPS Edition
- PHSS_26338

To determine whether a package is installed, enter a command similar to the following:

```
prompt> /usr/sbin/swlist -1 patch | grep PHKL_27813
```

Alternatively, to list all installed patches, enter the following command:

prompt> /usr/sbin/swlist -l patch | more

If a required patch is not installed, download it from the following URL and install it

```
http://itresourcecenter.hp.com
```

4. Make sure that Motif 2.1 Development Environment (X11MotifDevKit.MOTIF21-PRG) B.11.11.01 is installed.

To determine whether a bundle or product is installed, enter the following command:

```
prompt> /usr/sbin/swlist -l product | more
```

If a required product is not installed, you must install it. See your operating system or software documentation for information about installing products.

If the Motif package is not installed on the computer, create the symbolic links as follows:

- a. Log in as root.
- **b.** Change to the /usr/lib directory:

5. Create the required links:

```
prompt> ln -s libX11.3 libX11.sl
```

```
prompt> In -s libXIE.2 libXIE.sl
prompt> In -s libXext.3 libXext.sl
prompt> In -s libXhp11.3 libXhp11.sl
prompt> In -s libXi.3 libXi.sl
prompt> In -s libXm.4 libXm.sl
prompt> In -s libXp.2 libXp.sl
prompt> In -s libXt.3 libXt.sl
prompt> In -s libXt.3 libXt.sl
```

Make sure the /usr/lib/libCsup_v2.2 file has read permission for all. Login as root and set the permissions.

Checking Kernel Parameters

Verify that the kernel parameters shown in the following table are set either to the formula shown, or to values greater than or equal to the recommended value shown. The procedures following the table describe how to verify and set the values.

Parameter	Recommended Formula or Value
ksi_alloc_max	(nproc * 8)
max_thread_proc	3000
maxdsiz	2063835136 bytes
maxdsiz_64	2147483648 bytes
maxfiles	2048
maxfiles_lim	3861
maxssiz	134217728 bytes
maxssiz_64BIT	1073741824
maxswapchunks	16384
maxuprc	3686
maxusers	512
msgmap	6598
msgmax	32767
msgmnb	65535
msgmni	6846

Parameter	Recommended Formula or Value
msgseg	32767
msgtql	6596
msgssz	159
ncallout	6000
ncsize	((8 * nproc + 2048) + vx_ncsize)
nfile	163488
nflocks	4096
ninode	(8 * nproc + 2048)
nkthread	6000
nproc	4195
semmap	4098
semmni	4138
semmns	8360
semmnu	4092
semvmx	32767

Parameter	Recommended Formula or Value	
semume	42	
shmmni	530	
shmseg	32	
shmseg	32	
tcp_conn_request_max	2048	
vps_ceiling	64	

Note: If the current value for any parameter is higher than the value listed in this table, do not change the value of that parameter.

To view the current value specified for these kernel parameters, and to change them if necessary, follow these steps:

- **1.** Optionally, set the DISPLAY environment variable to specify the display of the local system:
 - Bourne, Bash, or Korn shell:

prompt> DISPLAY=localhost:0.0 ; export DISPLAY

C shell:

prompt> setenv DISPLAY localhost:0.0

2. Start System Administration Manager (SAM):

prompt> /usr/sbin/sam

- **3.** Choose the Kernel Configuration area, then choose the Configurable Parameters area.
- **4.** Check the value or formula specified for each of these parameters and, if necessary, modify that value or formula.

If necessary, see the SAM online help for more information about completing this step.

- **5.** Exit from SAM.
- **6.** If you modified the value specified for any parameter, reboot the system:

prompt> /sbin/shutdown -r now

If necessary, when the system restarts, log in and switch user to root.

Creating an Operating System Group for the Inventory Directory

You need to create operating system groups.

Create an Operating System Group for the Inventory Directory

If this is the first Oracle product to be installed on the computer, create an operating system group for the inventory directory. The installer creates files in the inventory directory to keep track of the Oracle products that are installed on the computer.

This guide uses the name oinstall for this group.

By having a separate group for the inventory directory, you allow different users to install Oracle products on the computer. Users need write permission for the inventory directory. They can achieve this by belonging to the oinstall group.

The default name of the inventory directory is oraInventory.

If you are unsure if there is already an inventory directory on the computer, look in the /home/oracle/oraInst.loc file. This file lists the location of the inventory directory and the group who owns it. If the file does not exist, the computer does not have Oracle products installed on it.

To create a local operating system group, enter the following command as the root user:

prompt> /usr/sbin/groupadd oinstall

For more information about operating system users and groups, see your operating system documentation or contact your system administrator.

Create an Operating System Group for Database Administration

Using the same steps in the previous section, create an operating system group called "dba". When you create an operating system user in the next step, you will set this dba group to be the secondary group of the user.

Creating an Operating System User

Create an operating system user to install and upgrade Oracle products. This guide refers to this user as the oracle user.

How to Create an User

To create the oracle operating system user as part of the oinstall group, enter the following command as the root user:

prompt> /usr/sbin/useradd -g oinstall oracle

For more information about operating system users and groups, see your operating system documentation or contact your system administrator.

Set the password for the oracle user by entering the following command and follow the instructions on screen:

prompt> passwd oracle

To check which groups an operating system user belongs to, use the groups command with the name of the user. For example:

prompt> groups oracle

Checking Environment Variables

The operating system user who will be installing Oracle Collaboration Suite needs to set (or unset) the following environment variables.

Table 2 Environment Variables

Environment Variable	Set or Unset
DISPLAY	Set it to the monitor where you want to the installer window to appear.
ORACLE_HOME	Must not be set.
ORACLE_SID	Must not be set.
TNS_ADMIN	Must not be set.
PATH, CLASSPATH, SHLIB_PATH, and LD_ LIBRARY_PATH	Must not contain references to directories in any Oracle home directories.
TMP and TMPDIR	Optional. If unset, defaults to /tmp.
ORA_NLS	Must not be set.

How to Set Environment Variables This section describes how to set environment variables:

Using the C shell:

prompt> setenv variable_name value

Example (C shell):

```
prompt> setenv DISPLAY test.mycompany.com:0.0
```

Using the Bourne or Korn shell:

```
prompt> variable name=value; export variable name
```

Example (Bourne or Korn shell):

```
prompt> DISPLAY=test.mydomain.com:0.0; export DISPLAY
```

Environment Variable Tips This section describes some things to look out for when setting environment variables:

- If you set environment variables in the .profile file, they might not be read. To ensure environment variables are set to the correct values, check their values in the shell where you will be running the installer.
- To check the value of environment variables, use the env command. This displays all the currently defined environment variables and their values.

```
prompt> env
```

If you use the su command to switch users (for example, switching from the root user to the oracle user), check the environment variables when you are the new user because the environment variables might not be passed to the new user. This can happen even if you use su with the - parameter (su - user).

```
prompt> /* root user */
prompt> su - oracle
prompt> env
```

Checking If Port 1521 Is in Use

This section is applicable only if you are installing Oracle Collaboration Suite Infrastructure.

The Oracle Collaboration Suite Infrastructure installs an Oracle database, which uses port 1521 by default.

To check if port 1521 is in use:

```
prompt> netstat -an | grep 1521
```

If port 1521 is in use by a third-party application, you need to configure the application to use a different port.

If port 1521 is in use by an existing Oracle database listener, you need to stop the listener before installing the Oracle Collaboration Suite Infrastructure.

See the *Oracle Collaboration Suite Installation Guide for hp-ux* for details.

Accessing the Welcome Page

After installation, access the Oracle Collaboration Suite Welcome page to verify that the installation was successful. The URL for the Welcome page is

http://hostname.domainname:http_port

Determine the http_port by looking in the ORACLE_ HOME/install/portlist.ini file. The port is listed on the "Oracle HTTP Server listen port" line.

Note: If you have multiple instances of Oracle Collaboration Suite installed on a computer, each instance has its own set of port numbers. Check the portlist.ini file in the correct Oracle home directory to be sure you are using the correct port numbers.

The Welcome page provides links to these useful pages:

- What is new in Oracle Collaboration Suite 10g Release 1 (10.1.2)
- Oracle Enterprise Manager Application Server Control ("Application Server Control"), which is a browser-based administrative tool
- Release Notes
- Demos

Additional Resources

For more information, see these Oracle resources:

- Oracle Collaboration Suite Documentation Library CD-ROM
- Oracle Collaboration Suite platform-specific documentation on Oracle Collaboration Suite documentation CD-ROM

Printed documentation is available for sale in the Oracle Store at

```
http://oraclestore.oracle.com
```

You can also contact your Oracle representative to purchase printed documentation.

To download free release notes, installation documentation, white papers, or other collateral, visit Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

```
http://www.oracle.com/technology/membership/
```

If you already have a user name and password for OTN, then you can go directly to the documentation section of OTN at

http://www.oracle.com/technology/documentation

Oracle Support Services

If you purchased Oracle Product Support, you can call Oracle Support Services for assistance. Oracle Support Services include phone assistance, version updates, and access to our service offerings. You have access to phone support 24 hours a day, 7 days a week. In the U.S.A., you can call Product Support at 1-800-223-1711

Make sure you have your CSI (CPU Support Identifier) number ready when you call. Keep the CSI number for your records, because it is your key to Oracle Support Services. The Oracle Store sends the CSI number to you in an e-mail alert when it processes your order. If you do not have your CSI number and you are in

the U.S.A., you can look up your CSI number by accessing our online Order Tracker, which provides detailed order information. Go to the Oracle Store and click on Order Tracker located above the top navigation bar.

For Oracle Support Services locations outside the U.S.A., call your local support center for information about how to access support. To find the local support center in your country, visit the Support Web Center at

http://www.oracle.com/support

At the Support Web Center you will find information about Oracle Support Services, such as:

- Contact information
- Instructions on how to access electronic services
- Helpful Web sites
- Support resources
- Oracle Support Portfolio
- Oracle Support Services news

With Oracle Product Support, you have round-the-clock access to Oracle MetaLink, the Oracle Support Services premier Web support

offering. Oracle MetaLink offers you access to installation assistance, product documentation, and a technical solution knowledge base.

It has technical forums, where you can post questions about your Oracle products and receive answers from Oracle Technical Support Analysts and other Oracle users. The questions and answers remain posted for the benefit of all users.

OracleMetaLink options include:

- Technical Assistance Request (TAR) access
- Patch downloads
- Bug database query access
- Product life-cycle information

You can access OracleMetaLink at

http://metalink.oracle.com

Version Updates

If you do not have a currently supported license, you can purchase the most recent version of an Oracle product from the Oracle Store at

http://oraclestore.oracle.com

If you do have a currently supported license, you can place non-urgent requests for Version Update shipments through the iTAR feature on Oracle *MetaLink*. You will need to log the iTAR type as a U.S. Client Relations/Non-Technical Request.

You can also request Version Update shipments in the U.S.A. by calling Client Relations. When requesting a Version Update, provide the following information to the Client Relations Analyst:

- CSI number
- Contact information
- Platform
- Product name
- Shipping address
- Version number of the product

Outside the U.S.A., call your local Oracle Support Center.

Premium Services

For information about our Premium Services, including onsite support, OracleGOLD, remote services, and upgrade packages, visit the Support Web Center at

http://www.oracle.com/support

or call your Support Sales Representative in the U.S.A. at 1-800-833-3536.

Quick Reference

Resource	Contact Information or Web Site
Oracle <i>MetaLink</i>	http://metalink.oracle.com
Purchase additional products, full-use licenses, version updates, and documentation in the U.S.A.	http://oraclestore.oracle.com
Access technical resources for developers	http://www.oracle.com/technology/index.html
Access all documentation	http://www.oracle.com/technology/documentation/collab.html

Resource	Contact Information or Web Site
Access information about technical support	http://www.oracle.com/support
Locate local Oracle Support Centers outside the U.S.A.	http://www.oracle.com/support
Locate local Oracle offices outside the U.S.A	http://www.oracle.com/global/index.html
Call Client Relations in the U.S.A.	1-800-223-1711
Speak with your sales representative in the U.S.A.	1-800-ORACLE-1
Obtain TTY access to technical support in the U.S.A.	1-800-446-2398